PRELIMINARY AMENDMENT

Serial Number: Unknown Filing Date: Herewith

Title: MICROCHIP MATRIX DEVICE FOR DUPLICATING AND CHARACTERIZING NUCLEIC ACIDS

Page 7 Dkt: 235.022US1

CLEAN VERSION OF PENDING CLAIMS

- 1. (Unchanged) Device for duplicating and characterizing nucleic acids in a reaction chamber, characterized in that a chamber body (1) containing an optically permeable chip (2) having a detection area (12), and being optically permeable at least in the zone of the detection area (12) of the chip (2), is sealingly placed on an optically permeable chamber support (5), so that a sample chamber (3) having a capillary gap (7) is formed between the chamber support (5) and the detection area (12) of the chip (2), which is temperature-adjustable and flow-controllable.
- 2. (Unchanged) Device according to claim 1, characterized in that the temperature adjustment means are connected with the chamber support(5) and permit a rapid heating and/or cooling of the sample chamber (3) having the capillary gap(7).
- 3. (Unchanged) Device according to claim 2, characterized in that the temperature adjustment means are situated on the side of the chamber support (5) facing towards the chamber body (1).
- 4. (Once Amended) Device according to claim 1, characterized in that the temperature adjustment means (16, 17) are configured in the form of optically transparent thin films and/or are so finely structured that the optical transparency of the chip (2) remains unaffected at least in the zones of the spots (13) of the detection area (12).
- 5. (Unchanged) Device according to claim 4, characterized in that the temperature adjustment means comprise micro-structured heating elements (17), preferably nickel-chromium thick film resistance heaters and/or microstructured temperature sensors (16), preferably nickel-chromium thick film resistance sensors.

Page 8 Dkt: 235.022US1

Citle: MICROCHIP MATRIX DEVICE FOR DUPLICATING AND CHARACTERIZING NUCLEIC ACIDS

6. (Once Amended) Device according to claim 1, characterized in that the chamber support (5) comprises systems for thoroughly mixing the liquid sample, which are configured in the form of optically transparent thin films and/or are so finely structured that the optical transparency of the chip (2) remains unaffected at least in the zones of the spots (13) of the detection area (12), whereby preferably a quadrupole system for inducing an electro-osmotic flow is concerned.

- 7. (Unchanged) Device according to claim 6, characterized in that the quadrupole system is realized as gold-titanium electrodes.
- 8. (Once Amended) Device according to claim 1, characterized in that the chamber support (5) and the chamber body (1) preferably consist of glass and/or synthetic material and/or optically permeable synthetic materials particularly preferred of nylon, Teflon, topaz, polycarbonate, polystyrene, PMMA and/or polymethane ethyl acrylate.
- 9. (Once Amended) Device according to claim 1, characterized in that the chamber support (5) consists of a thermally conducting material.
- 10. (Once Amended) Device according to claim 1, characterized in that the chip consists of optically permeable materials, preferably of glass, borofloat glass, quartz glass, monocrystalline CaF₂, sapphire, PMMA and/or silicon.
- 11. (Once Amended) Device according to claim 1, characterized in that the chamber body (1) comprises, at least in the zone of the chip (2) an optically permeable conical recess.
- 12. (Once Amended) Device according to claim 1, characterized in that the chamber body disposes of an inlet (81) and an outlet (82) spatially separate from each other, for charging the sample chamber (3) and the capillary gap (7).

- Device according to claim 1, (Once Amended) 14. characterized in that the chamber body (1) is sealingly and unreleasably connected with the chamber support (5) by an adhesive and/or weld connection, or is releasably connected through an additional sealing surface (43).
- Device according to claim 1, 15. (Once Amended) characterized in that the detection area (12) is configured in the form of spots, onto which probes (56, 57, 58, 59) in the form of nucleic acid molecules are immobilized, said nucleic acid molecules preferably being DNA molecules and/or RNA molecules.
- (Unchanged) Device according to claim 15, 16. characterized in that the probes (56, 57, 58, 59) are immobilized through spacers (55).
- (Once Amended) Device according to 17. claim 1, characterized in that the detection area (12) is configured in the form of spots, onto which probes (56, 57, 58, 59) in the form of peptides and/or proteins are immobilized, preferably antibodies, receptor molecules, hormones and/or pharmaceutically active peptides being concerned.
- Device according to claim 1, (Once Amended) 18. characterized in that the evaluation of the chip-based characterization may ensue by forms of the optical detection and/or spectroscopy, particularly preferred by transmitted-light fluorescence measurement, dark field fluorescence measurement, confocal fluorescence measurement, reflected-light fluorescence measurement, photometry and/or differential photometry.

PRELIMINARY AMENDMENT

Serial Number: Unknown

Filing Date: Herewith

Title: MICROCHIP MATRIX DEVICE FOR DUPLICATING AND CHARACTERIZING NUCLEIC ACIDS

Page 10 Dkt: 235.022US1

- 19. (Once Amended) Device according to claim 1, characterized in that the evaluation of the chip-based characterization ensues by a silver precipitation reaction.
- 20. (Once Amended) Use of a device according to claim 1 for an almost simultaneous performance of reprocessing reactions and/or conditioning reactions and a chip-based characterization of the products.
- 21. (Unchanged) Use of a device according to claim 20, the reprocessing reaction and/or conditioning reaction concerning an amplification of nucleic acids by PCR.
- 22. (Unchanged) Use of a device according to claim 20, the reprocessing reaction and/or conditioning reaction concerning a reverse transcription of RNA to cDNA.
- 23. (Once Amended) Use of a device according to claim 1, the reprocessing reaction and/or conditioning reaction concerning a digestive process of nucleic acids by means of restriction enzymes.
- 24. (Unchanged) Use of a device according to claim 20 for the almost simultaneous amplification of DNA by PCR and for the chip-based characterization of the PCR products.